

TECHNICAL DATA SHEET

OAK BATHROOM COUNTERTOPS

WOOD SPECIES:



ASSORTMENT DESCRIPTION:

CATEGORY	oak bathroom countertops/ finger-jointed wood panels
APPLICATIONS	vanity top, shelf, sink surround
DIMENSIONS	thickness: 15-100 mm (above 45 mm optionally layered gluing) width: up to 1300 mm length: up to 6100 mm
QUALITY	AB, AC, BC
LONGITUDINAL JOINTING	D4 glue
EDGE GLUING	standard glue D4
MOISTURE CONTENT	KD 9% +/- 2% according to the standard EN 15497:2014 (finger jointed solid timber)
LAMELLA WIDTHS	38 - 45 mm (standard) / 15 - 90 mm (optional)
SANDING	grit 150
OILING	double-coated with hard wax oil (final oiling)
PROCESSING OPTIONS	cut to size, edge profiling, drilling, machining on CNC
CERTIFICATIONS	FSC®, PEFC, EPD
CHEMICAL RESISTANCE	in compliance with DIN 68861-1
BENDING STRENGTH	40 N/mm² EN 408:2010+A1:2012
BONDING QUALITY	results available on demand / EN13354:2008
REACH	compliant



Edwood Sp. z o.o.
86 Łomaska Street, 21-500 Biała Podlaska, Poland
edwood@edwood.pl
www.edwood.pl



TECHNICAL DATA SHEET

KITCHEN COUNTERTOPS

WOOD SPECIES:



ASSORTMENT DESCRIPTION:

CATEGORY	kitchen countertops / finger-jointed wood panels
APPLICATIONS	kitchen countertops, shelf, table components
DIMENSIONS	thickness: 15-100 mm (above 45 mm optionally layered gluing) width: up to 1300 mm length: up to 6100 mm
QUALITY	AB, AC, BC, CC
LONGITUDINAL JOINTING	D4 glue
EDGE GLUING	standard glue D3
LAMELLA WIDTHS	38 - 45 mm (standard)

MOISTURE CONTENT	KD 9% +/- 2% according to the standard EN 15497:2014 (finger jointed solid timber)
SANDING	grit 120
OILING	no oiling or pre-oiling or final oiling
PROCESSING OPTIONS	cut to size, edge profiling, drilling, machining on CNC
CERTIFICATIONS	FSC®, PEFC, EPD
CHEMICAL RESISTANCE	in compliance with DIN 68861-1
BENDING STRENGTH	40 N/mm ² EN 408:2010+A1:2012
REACH	compliant



Edwood Sp. z o.o.
86 Łomaska Street, 21-500 Biata Podlaska, Poland
edwood@edwood.pl
www.edwood.pl

