



TECHNICAL DATA SHEET

ACOUSTIC WOODEN WALL PANELS

WOOD SPECIES:



FINISHING:



ASSORTMENT DESCRIPTION:

CATEGORY	acoustic wooden wall panels
APPLICATIONS	internal finishes of walls, partitions and ceilings
DIMENSIONS	600 x 2400/2700/3000 mm
QUALITY	solid wood AB, BC, rustic
PET FELT THICKNESS	9 mm
EDGE GLUING	standard glue D3 - D4 optional
MOISTURE CONTENT	KD 9% +/- 2% according to the standard EN 15497:2014
SANDING	grit 150
PROCESSING OPTIONS	cut to size, oiling, lacquering
CERTIFICATIONS	FSC®, PEFC, EPD
FORMALDEHYDE	in compliance with E1 PN-EN 717-1:2006
SOUND ABSORPTION	in compliance with E PN-EN 1793-5:2016-05
REACTION TO FIRE	in compliance with E-s2, d1 PN_EN 13823+A1:2022
REACH	compliant



TECHNICAL DATA SHEET

ACOUSTIC WOODEN WALL PANELS

PROFILE TYPES:

<p>30 mm</p> <p>20 mm</p> <p>WOOD SPECIES:</p> <ul style="list-style-type: none"> • Oak Prime • Oak Natural <p>NUMBER OF SLATS: 14</p> <p>DISTANCE BETWEEN SLATS: 12,9 mm</p>	<p>42 mm</p> <p>15 mm</p> <p>WOOD SPECIES:</p> <ul style="list-style-type: none"> • Oak Natural <p>NUMBER OF SLATS: 9</p> <p>DISTANCE BETWEEN SLATS: 24,7 mm</p>	<p>25 mm</p> <p>25 mm</p> <p>WOOD SPECIES:</p> <ul style="list-style-type: none"> • Oak Prime/Rustic • Oak Natural <p>NUMBER OF SLATS: 12</p> <p>DISTANCE BETWEEN SLATS: 25 mm</p>	<p>43 mm</p> <p>21 mm</p> <p>WOOD SPECIES:</p> <ul style="list-style-type: none"> • Oak Prime/Rustic • Ash Mosaic • Maple • European Walnut • Light Ash <p>NUMBER OF SLATS: 9</p> <p>DISTANCE BETWEEN SLATS: 23,7 mm</p>
--	--	---	--



Edwood Sp. z o.o.
86 Łomaska Street, 21-500 Biała Podlaska, Poland
edwood@edwood.pl
www.edwood.pl

